

SALIENT FEATURES

- Can be provided with water jacketing when milling heat sensitive products.
- Available in various combinations to suit specific requirements.
- Knife or impact blades for granulation or pulverising.
- Reversing starter provided for dual operation.
- All contact parts in stainless steel to avoid contamination.
- Availability of various screen sizes
- operation completely dustless.
- Advanced rugged design, requires very little maintenance.
- Easy to clean and operate on various kinds of products.
- Dynamically balanced rotor to ensure smooth running even at highest speed.



Comminuting Mill

The versatile comminuting machine that has proved its worth in the chemical and pharmaceutical industry for

- Wet and dry granulation
- Pulversing
- Wetting and Dispersion
- Ointment milling
- Sizing of crude drugs

TECHNICAL SPECIFICATIONS

Rotor Speed	: 1000-2250-4500 rpm
Blades	: Swinging type with knife and impact edge
Screens	: Perforated sheet / woven wire mesh
Electric Motor	: 7.5 hp., 1440 rpm, 440 v, 50 Hz, 3 Phase
Overall Dimensions	: 690 long x 1270 wide x 1700 mm height
Net Weight	: 310 kgs.
Output (Kg./Hr.)	: 25 to 300 (depending on product, rotor speed and screen)

Specifications, Features are subject to changes without notice.

JICON MACHINES
PRIVATE LIMITED



JICON EXPORTS

P. O. Box 8902, Mumbai - 400 072, India. Tel.: (+91)(22) 2851 0398 • Fax : (+91)(22) 2851 6488
E-mail : jicon.ind@vsnl.com • Website : <http://www.jicon.com>

COMMINUTING MILL